

Hタイプパイプベンダー 標準仕様

仕様 Specifications		型式 Model							
		TB-DR-035HA TB-DR-035HANC	TB-DR-1HA TB-DR-1HANC	TB-DR-2HA TB-DR-2HANC	TB-DR-3HANC	TB-DR-4HANC	TB-DR-6HANC	TB-DR-6HTANC	TB-DR-8HANC
曲げ管最大外径×肉厚(mm) Max. pipe OD x Wall thickness		φ34.0×t3.2	φ42.7×t3.5	φ60.5×t5.5	φ89.1×t7.6	φ114.3×t8.6	φ165.2×t5.0	φ165.2×t11.0	φ216.3×t12.7
曲げ半径最大(mm) Max. bending radius		R150	R250	R300	R500	R700	R800	R800	R1100
曲げ角度最大(°) Max. bending angle maximum		180	180	180	180	180	180	180	180
曲げ角度選択数 Bending angle selections	HA手動 Manual	4	6	6	—	—	—	—	—
	HANCタッチパネル Touch panel	4工程×30チャンネル 4 steps×30 channels							
曲げ正転時間(sec./180°)高速/低速 Normal rotation bending time High speed/Low speed		— / 4	4 / 5	7 / 11	9 / 16	17 / 23	— / 60	— / 60	— / 120
曲げ戻り時間(sec./180°) Reverse rotation time		— / 3	3 / 3	5 / 5	4 / 5	12 / 17	— / 40	— / 40	— / 50
芯金有効長(mm) Effective mandrel length		1350	1700	2000	3000	5500	5500	5500	6000
油圧ポンプ用モーター(kW) Hydraulic pump motor		2.2	3.7	5.5	7.5	11.0	15.0	18.5	22.0
電源電圧 Power-supply voltage		3φ AC 200V							
総合電気容量(kVA) Electric capacity		10.4	10.4	13.9	17.3	20.8	—	—	—
作動油タンク容量(L) Hydraulic oil tank		60	100	150	250	300	400	400	580
機械大きさ 全長/全幅/全高(mm) Dimensions Length/Width/Height		1950/800/1000	2500/850/1000	3000/950/1110	4180/1470/1130	6840/1760/1320	7320/2100/1350	7400/2100/1600	8100/3200/2500
機械重量(kg) Weight	HA	650	1150	1850	—	—	—	—	—
	HANC	650	1200	1900	3600	5500	9100	11000	25100